



DESCRIZIONE

Illuminatori realizzati in guida d'onda circolare di tipo "cassegain" coprono tutte le bande di frequenza tipicamente utilizzate per i ponti radio terrestri, da 4 a 15 GHz.

Sono disponibili sia in singola che in doppia polarizzazione e per diametri di antenne paraboliche da 60 a 300 cm.

L'illuminatore viene fornito, previa specifica del cliente, con il connettore "N" in ingresso che in flangia.

A richiesta del cliente è possibile realizzare prodotti custom per l'adattamento a parabole con specifiche meccaniche (dimensione, fuoco e foro) e connettore diversi.



DESCRIPTION

These feeders "cassegain" are produced in circular waveguide and cover all frequency band used in microwave transmission, from 4 to 15 GHz.

Feeders are available both in single and double polarization for parabolic dishes from 60 to 300 cm.; they are provided with "N" connector or with flange as requested by customer.

It's possible to realize and adjust custom range frequency feeders for different parabolic dishes, with different mechanical specifications and connectors type.

14,0 ÷ 15 GHz
CASSEGRAIN
CODE.: GCN \ GCF - 040\045\050\058\064\069\076\080\100\140 - S\D
ILLUMINATORI
FEEDERS



Geritel

Geritel s.r.l. - via Postumia s.n. - 15057 - Tortona (AL) - ITALY

TEL: +39 0131 813533 FAX: +39 0131 890016 - info@geritel.com - www.geritel.com

	Banda di frequenza [GHz] <i>Frequency band [GHz]</i>	Polarizzazione <i>Polarization</i>	Dimensioni e peso <i>Dimensions and weight</i>
GCN040S / GCF040S GCN040D / GCF040D	4.0 – 4.5	S / D	Vari per parabole da 60 cm a 3 m di diametro. <i>Various, for parabolic reflectors with diameters from 2 feet to 10 feet.</i>
GCN045S / GCF045S GCN045D / GCF045D	4.5 – 5.0	S / D	
GCN050S / GCF050S GCN050D / GCF050D	5 – 6.0	S / D	
GCN058S / GCF058S GCN058D / GCF058D	5.8 – 6.4	S / D	
GCN064S / GCF064S GCN064D / GCF064D	6.4 – 7.0	S / D	
GCN069S / GCF069S GCN069D / GCF069D	6.9 – 7.6	S / D	
GCN076S / GCF076S GCN076D / GCF076D	7.6 – 8.4	S / D	
GCN080S / GCF080S GCN080D / GCF080D	8.0 – 9.0	S / D	
GCN100S / GCF100S GCN100D / GCF100D	10 – 13	S / D	
GCN140S / GCF140S GCN140D / GCF140D	14 – 15	S / D	

